

L-ALLE















HANDRAIL







The mark of sponsible forestry



L-ALLE 47 X 21.5

1.02 in

The L-ALLE loft ladder has got single sealing and hatch thickness 1.02 in. The L-ALLE model is ideal for environment where the attic is insulated and does not require additional thermal insulation. L-ALLE loft ladder model is equipped with 4 – section ladder, due to it is ideal for montage in high rooms up to 130 in. Our non-slip feet included in L-ALLE loft ladder provide an aesthetic finish for the ladder after cutting. The excellent quality of materials used for the production of stairs and attention to every details of finish cause that the stairs will satisfy even the most demanding customers. To increase security and for comfortable use our L-ALLE ladder is also equipped with stable and durable handrail. In the interest of user convenience, the handrail has been designed in such a way that it can be mounted on the left or right side depending on customer preferences. The excellent quality of materials used for the production of stairs and attention to every details of finish cause that the stairs will satisfy even the most demanding customers . The maximum load when using stairs is up to 352 lbs.

Technical specification

Insulated hatch thickness	1.02 in
Thickness of thermal insulation	0.79 in
Hatch colour from both sides	White
Wooden ladder	4 sections
Height of wooden box	5.31 in
Width of ladder	15.7 in
Width of step	14.1 in
Depth of step	3.15 in
Landing space	67.7 in
Opening distance/angle	66.1 in
Maximum ceiling height	130 in

Box dimensions [in] AxB

47 x 21.5 AS. 47.24 x 21.65

Outer box dimensions, mounting opening 0.79 in larger

Non-standard dimensions

Min - Max Length 47 - 55.1 in Min - Max Width 21.3 - 33.5 in

*Unusual dimensions available in full size of untypical stairs can not exceed 10.76 ft²

Accessories








Masking batten

Mounting system

Hatch balustrade

Technical draw



C	130 in
D	67.7 in
E	66.1 in
G	352 lbs

